

وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h)										* توان نامی Nom. Power		موتور Motor	پمپ Pump		
			آبدهی										HP	kW				
			13	12	11	10	9*	8	7	6	0	ارتفاع (m)						
60	8	1250	26	30	32	33	34	35	37	38	48	2	1.5	6C	152/4			
67	8	1365	37	45	47	49	50	52	55	57	71	3	2.2	6C	152/6			
76	8	1530	60	66	68	70	74	76	80	82	101	4	3	6C	152/9			
90	8	1965	62	69	76	83	87	92	96	101	122	5	3.7	6E	152/11			
104	8	1910	78	87	95	105	111	116	123	125	155	7.5	5.5	6E	152/14			
111	8	2040	91	104	113	124	132	142	148	154	187	7.5	5.5	6E	152/17			
124	8	2240	114	126	138	149	160	168	177	181	218	10	7.5	6E	152/20			
133	8	2370	140	156	170	182	194	203	214	219	266	10	7.5	6E	152/23			
173	10	2605	176	195	214	232	247	260	273	282	340	12.5	9.2	7A	152/30			
207	10	3030	205	230	251	273	292	310	325	335	405	15	11	7A	152/38			

\* \*\* Ref to page 25

\* \*\* رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	2 Inch	* قطر لوله خروجی	Check Valve	1 1/2-11 Inch	رزه سویاپ
------------------	--------	------------------	-------------	---------------	-----------

* وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h)								* توان نامی Nom. Power		موتور Motor	پمپ Pump				
			آبدهی								HP	kW						
			100	90	80	70*	60	50	40	0					ارتفاع (m)			
130	10	1600	16.5	20	23	26	28	29	30	33	10	7.5	6E	345/1				
183	10	1780	33	40	46	52	56	58	60	66	20	15	7A	345/2				
215	10	1990	49.5	60	69	78	84	87	90	99	30	22	7A	345/3				
303	320	10	12	2480	2200	66	80	92	104	112	116	120	132	41	30	8A	9A	345/4
331	353	10	12	2640	2380	82.5	100	115	130	140	145	150	165	50	37	8A	9A	345/5
369	386	10	12	2895	2555	99	120	138	156	168	174	180	198	62	45.5	8A	9A	345/6
403	397	10	12	3195	2705	115.5	140	161	182	196	203	210	231	75	55	8A	9A	345/7
430	445	12	2790	2860	132	160	184	208	224	232	240	264	85	62.5	9B	9A	345/8	
458	480	12	2985	3085	148.5	180	207	234	252	261	270	297	100	73.5	9B	9A	345/9	
469	491	12	3060	3160	165	200	230	260	280	290	300	330	100	73.5	9B	9A	345/10	
502	543	12	3240	3190	181.5	220	253	286	308	319	330	363	125	92	9B	10A	345/11	
513	554	12	3320	3270	198	240	276	312	336	348	360	396	125	92	9B	10A	345/12	
578	612	12	3625	3550	214.5	260	299	338	364	377	390	429	150	110	9B	10A	345/13	
589	623	12	3700	3625	231	280	322	364	392	406	420	462	150	110	9B	10A	345/14	
821	848	12	3930	3985	247.5	300	345	390	420	435	450	495	177	130	10A	12A	345/15	
832	859	12	4010	4060	264	320	368	416	448	464	480	528	177	130	10A	12A	345/16	
895	14	4210	280.5	340	391	442	476	493	510	510	561	204	150	12A	12A	345/17		
906	14	4290	297	360	414	468	504	522	540	594	204	150	12A	12A	345/18			
917	14	4365	313.5	380	437	494	532	551	570	627	204	150	12A	12A	345/19			
958	14	4540	330	400	460	520	560	580	600	660	251	185	12A	12A	345/20			

\* \*\* Ref to page 25

\* \*\* رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	4 Inch	* قطر لوله خروجی	Check Valve	4-11 Inch	رزه سویاپ
------------------	--------	------------------	-------------	-----------	-----------

☆ وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h)								☆ توان نامی Nom. Power		موتور Motor	پمپ Pump			
			آبدهی								HP	kW					
			65	55	50	45*	40	35	30	0							
104	10	1580	22	29	32	34	37	38	40.5	10	7.5	6E	293/2				
139	10	1650	33	43.5	48	51	55.5	57	61	15	11	7A	293/3				
157	10	1815	44	58	64	68	74	76	81	20	15	7A	293/4				
178	10	1960	55	72.5	80	85	92.5	95	101	25	18.5	7A	293/5				
190	10	2075	66	87	96	102	111	114	121.5	30	22	7A	293/6				
196	10	2140	72	97	107	113	121	125	131	30	22	7A	293/7a(126)				
243	10	2360	2205	77	101.5	112	119	129.5	133	33	24.5	8A	9A	293/7			
274	291	10	12	2620	2340	88	116	128	136	148	152	162	41	30	8A	9A	293/8
280	297	10	12	2685	2405	99	130.5	144	153	166.5	171	182	41	30	8A	9A	293/9
303	325	10	12	2830	2570	110	145	160	170	185	190	202.5	50	37	8A	9A	293/10
309	331	10	12	2895	2635	121	159.5	176	187	203.5	209	223	50	37	8A	9A	293/11
342	359	10	12	3130	2800	132	174	192	204	222	228	243	62	45.5	8A	9A	293/12
388	382	10	12	3415	2935	143	188.5	208	221	240.5	247	263	75	55	8A	9A	293/13
394	388	10	12	3480	3000	154	203	224	238	259	266	283.5	75	55	8A	9A	293/14
400	394	10	12	3545	3065	165	217.5	240	255	277.5	285	304	75	55	8A	9A	293/15
411	426	12		3205	3275	176	232	256	272	296	304	324	85	62.5	9B	9A	293/16
417	432	12		3270	3340	187	246.5	272	289	314.5	323	344	85	62.5	9B	9A	293/17
440	462	12		3450	3550	198	261	288	306	333	342	364.5	100	73.5	9B	9A	293/18
446	468	12		3510	3610	209	275.5	304	323	351.5	361	385	100	73.5	9B	9A	293/19
452	474	12		3570	3670	220	290	320	340	370	380	405	100	73.5	9B	9A	293/20
458	480	12		3630	3730	231	304.5	336	357	388.5	399	425	100	73.5	9B	9A	293/21

☆ ☆ ☆ Ref to page 25

☆ ☆ ☆ رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	4 Inch	* قطر لوله خروجی	Check Valve	3-11 Inch	رزه سوپاپ
------------------	--------	------------------	-------------	-----------	-----------

☆ وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h)						☆ توان نامی Nom. Power		موتور Motor	پمپ Pump			
			آبدهی						HP	kW					
			30	25	20*	15	0								
92	10	1420	24	29	32	35	40	5	3.7	6E	233/2				
105	10	1560	36	43.5	48	52.5	60	7.5	5.5	6E	233/3				
116	10	1680	48	58	64	70	80	10	7.5	6E	233/4				
141	10	1665	60	72.5	80	87.5	100	12.5	9.2	7A	233/5				
157	10	1800	72	87	96	105	120	15	11	7A	233/6				
169	10	1895	84	101.5	112	122.5	140	18	13	7A	233/7				
181	10	2015	96	116	128	140	160	20	15	7A	233/8				
202	10	2150	108	130.5	144	157.5	180	25	18.5	7A	233/9				
208	10	2210	120	145	160	175	200	25	18.5	7A	233/10				
214	10	2265	132	159.5	176	192.5	220	25	18.5	7A	233/11				
226	10	2375	144	174	192	210	240	30	22	7A	233/12				
279	306	10	12	2645	2495	158	188.5	208	227.5	260	33	24.5	8A	9A	233/13
285	312	10	12	2750	2555	168	203	224	245	280	33	24.5	8A	9A	233/14
316	333	10	12	2965	2740	180	217.5	240	262.5	300	41	30	8A	9A	233/15
322	339	10	12	3020	2795	192	232	256	280	320	41	30	8A	9A	233/16
328	345	10	12	3080	2850	204	246.5	272	297.5	340	41	30	8A	9A	233/17
351	373	10	12	3270	3010	216	261	288	315	360	50	37	8A	9A	233/18
357	379	10	12	3330	3070	228	275.5	304	332.5	380	50	37	8A	9A	233/19
363	385	10	12	3385	3125	240	290	320	350	400	50	37	8A	9A	233/20
369	391	10	12	3440	3180	252	304.5	336	367.5	420	50	37	8A	9A	233/21

☆ ☆ ☆ Ref to page 25

☆ ☆ ☆ رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	3 Inch	* قطر لوله خروجی	Check Valve	3-11 Inch	رزه سوپاپ
------------------	--------	------------------	-------------	-----------	-----------



وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h) آبدهی										* توان نامی Nom. Power		موتور Motor	پمپ Pump	
			330	300	240	210*	180	150	120	0	HP	kW					
			Head (m) ارتفاع														
309	315	12	1990	2020	17	21	28	32	34	35	37	41	41	30	9B	9A	435/1a(177/171)
320	337	12	2040	2120	25	29	33	36	40	41	42	47.5	50	37	9B	9A	435/1
370	387	12	2300	2380	28	36	44	56	60	64	66	76	62	45.5	9B	9A	435/2a(167/161)
389	404	12	2380	2450	36	45	59.5	65.5	69.5	72	74.5	83	75	55	9B	9A	435/2a(178/172)
409	424	12	2460	2530	44	53	67	72.5	74.5	77.5	79	90	85	62.5	9B	9A	435/2a(185/179)
426	448	12	2575	2675	50	58	72	76	80	82	84	95	100	73.5	9B	9A	435/2
454	476	12	2740	2840	42	54	75	84	90	96	99	114	100	73.5	9B	9A	435/3a(171/166)
476	517	12	2840	2790	51	63	84	96	102	105	111	123	125	92	9B	10A	435/3a(177/171)
476	517	12	2840	2790	66	79.5	100.5	109	112	116	118.5	135	125	92	9B	10A	435/3a(185/179)
509	553	12	2990	2915	75	87	108	114	120	123	126	142.5	150	110	9B	10A	435/3
537	581	12	3155	3080	68	84	112	128	136	140	148	164	150	110	9B	10A	435/4a(177/171)
757	784	12	3180	3280	82	98	127.5	139	146	150	154	176	177	130	10A	12A	435/4a(183/177)
809		14	3350		100	116	144	152	160	164	168	190	204	150	12A		435/4
837		14	3515		102.5	122.5	159.5	174	182.5	187.5	192.5	220	204	150	12A		435/5a(183/177)
867		14	3615		125	145	180	190	200	205	210	237.5	252	185	12A		435/5
916	1250	14	3830	4010	150	174	216	228	240	246	252	285	300	220	12B	14B	435/6
944	1278	14	3995	4175	143.5	171.5	223	243	255.5	262.5	269.5	308	300	220	12B	14B	435/7a(183/177)
1500		16	4875		225	261	324	342	360	369	378	427.5	476	350	14B		435/9
1528		16	5040		250	290	360	380	400	410	420	475	476	350	14B		435/10

\* \* \* Ref to page 25

\* \* \* رجوع شود به صفحه 20

Outlet Pipe Dia. 8 Inch	* قطر لوله خروجی	Check Valve 6-11 Inch	رزه سوپاپ
-------------------------	------------------	-----------------------	-----------

وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h) آبدهی										* توان نامی Nom. Power		موتور Motor	پمپ Pump	
			450	400	350*	300	250	200	150	0	HP	kW					
			Head (m) ارتفاع														
338	344	12	1970	2000	-	16	22	26	29	31	33.5	41	41	30	9B	9A	466/1a(179/170)
349	366	12	2020	2100	-	20	25	30	33	34	38	44	50	37	9B	9A	466/1a(185/176)
349	366	12	2070	2100	18	24	30	34	36	37	40	47	50	37	9B	9A	466/1a(191/182)
371	388	12	2120	2200	23	29	34	38	39	40	43	50	62	45.5	9B	9A	466/1a(197/188)
390	405	12	2200	2270	32	37	42	44	45	47	50	56	75	55	9B	9A	466/1
442	457	12	2460	2530	-	32	44	52	58	62	67.5	82	85	62.5	9B	9A	466/2a(179/170)
459	481	12	2570	2670	-	40	50	60	66	68	76	88	100	73.5	9B	9A	466/2a(185/176)
481	522	12	2670	2620	36	48	60	68	72	74	80	94	125	92	9B	10A	466/2a(191/182)
481	522	12	2670	2620	46	58	68	72	78	80	86	100	125	92	9B	10A	466/2a(197/188)
514	558	12	2820	2740	52	63	73.5	80	83.5	86.5	91.5	106	150	110	9B	10A	466/2a(203/194)
514	558	12	2820	2740	64	74	84	88	90	94	100	112	150	110	9B	10A	466/2
766	793	12	3180	3110	69	87	102	114	117	120	129	150	177	130	10A	12A	466/3a(197/188)
818		14	3180		79	97	112	120.5	123.5	128	135	172	204	150	12A		466/3a(203/194)
848		14	3280		99	111	126	132	135	141	150	168	252	185	12A		466/3
901	1235	14	3505	3635	128	148	168	176	180	188	200	224	300	220	12B	14B	466/4
933	1267	14	3780	3810	115	145	170	190	195	200	215	250	300	220	12B	14B	466/5a(197/188)
1337		16	3930		132	163	190	202	212	223	236.5	275	354	260	14B		466/5a(207/197)

\* \* \* Ref to page 25

\* \* \* رجوع شود به صفحه 20

Outlet Pipe Dia. 8 Inch	* قطر لوله خروجی	Check Valve 8-10 Inch	رزه سوپاپ
-------------------------	------------------	-----------------------	-----------

☆ وزن کل Total Weight (kg)	☆ قطر چاه Well Dia. (In)	☆ طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h) آبدی											☆ توان نامی Nom. Power		☆ موتور Motor	☆ پمپ Pump	
			240	220	200	180*	160	140	120	100	0	HP	kW					
			Head (m) ارتفاع															
243	270	12	2072	1920	24	26.5	29	31	32.5	33	33.5	34	41.5	33	24.5	8A	9A	425/1
299	305	12	2120	2150	30	35	40	44	47	49.5	51	52	64	41	30	9B	9A	425/2a(155/147)
310	327	12	2070	2150	39	44	49	52.5	55.5	57.5	58	59	71	50	37	9B	9A	425/2a(167/159)
332	349	12	2270	2350	45	50.5	54.5	58.5	61.5	63.5	64	65	81	62	45.5	9B	9A	425/2a(173/165)
351	366	12	2345	2420	48	53	58	62	65	66	67	68	85	75	55	9B	9A	425/2
371	386	12	2510	2580	55.5	63	70.5	76	80.5	84	85	86.5	107	75	55	9B	9A	425/3a(167/157)
391	406	12	2590	2660	62.5	70.5	77	83	87	90	91.5	93	115	85	62.5	9B	9A	425/3a(170/162)
408	430	12	2700	2800	72	79.5	87	93	97.5	99	100.5	102	124	100	73.5	9B	9A	425/3
428	450	12	2880	2960	74	84	94	101	107.5	112.5	113.5	115.5	143	100	73.5	9B	9A	425/4a(165/157)
450	527	12	2960	2910	91	100.5	110	118	123	127	128.5	130	162	125	92	9B	10A	425/4a(173/165)
450	527	12	2960	2910	96	106	116	124	130	132	134	136	170	150	110	9B	10A	425/4
503	547	12	3190	3190	104.5	117.5	128.5	138.5	145	150	152.5	155	192	150	110	9B	10A	425/5a(170/162)
503	547	12	3270	3190	114	126.5	138	147	155	159	160.5	162.5	203	150	110	9B	10A	425/5a(173/165)
523	567	12	3430	3350	119.5	127	142	155	164	171.5	173.5	176.5	219	150	110	9B	10A	425/6a(165/157)
743	770	12	3480	3530	125	141	155	166	174	180	183	186	231	177	130	10A	12A	425/6a(170/162)
795	14	3600	144	159	174	186	195	198	201	204	249	204	150	12A			425/6	
815	14	3760	159	177	192.5	205.5	216.5	222.5	224.5	227.5	284	204	150	12A			425/7a(173/165)	
845	14	3860	168	185.5	203	217	227.5	231	234.5	238	291	252	185	12A			425/7	
885	14	4020	184	192	216	232	240	249.5	255	260	320	252	185	12A			425/8a(173/165)	
956	1290	14	4070	4200	192	212	232	248	260	264	268	272	332	300	220	12B	14B	425/8
976	1310	14	4230	4360	216	238.5	261	279	292.5	297	301.5	306	378	300	220	12B	14B	425/9

☆ ☆ ☆ Ref to page 25

☆ ☆ ☆ رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	6 Inch	☆ قطر لوله خروجی	Check Valve	6-11 Inch	رزه سوپاپ
------------------	--------	------------------	-------------	-----------	-----------

☆ وزن کل Total Weight (kg)	☆ قطر چاه Well Dia. (In)	☆ طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h) آبدی								☆ توان نامی Nom. Power		☆ موتور Motor	☆ پمپ Pump			
			180	160	140	120*	100	80	60	0	HP	kW					
			Head (m) ارتفاع														
149	10	1630	14.5	18.5	22	24	26	27	28	32	18	13	7A	374/1			
249	276	10	2180	2065	29	37	44	48	52	54	56	64	33	24.5	8A	9A	374/2
312	334	10	2640	2380	37.5	49.5	58.5	69	73.5	76.5	80	90	50	37	8A	9A	374/3a(149/144)
312	334	10	2640	2380	43.5	55.5	66	72	78	81	84	96	50	37	8A	9A	374/3
355	372	10	2950	2620	54.5	70	84	94.5	102	106	109	124	62	45.5	8A	9A	374/4a(152/147)
411	405	10	3310	2830	68.5	87.5	105	118.5	127.5	132.5	136.5	155	75	55	8A	9A	374/5a(152/147)
411	405	10	3310	2830	72.5	92.5	110	120	130	135	140	160	75	55	8A	9A	374/5
426	441	12	2980	3045	76	98	116	133	145	153	158	180	85	62.5	9B	9A	374/6a(149/144)
443	465	12	3090	3190	87	111	132	144	156	162	168	192	100	73.5	9B	9A	374/6
459	481	12	3230	3330	87.5	117	140	155.5	170	178	184	210	100	73.5	9B	9A	374/7a(149/144)
481	522	12	3330	3280	101.5	129.5	154	168	182	189	196	224	125	92	9B	10A	374/7
497	538	12	3470	3420	116	148	176	192	208	216	224	256	125	92	9B	10A	374/8
562	606	12	3760	3640	130.5	166.5	198	216	234	243	252	288	150	110	9B	10A	374/9
798	825	12	3900	3780	137	175	210	237	255	265	273	310	150	110	9B	10A	374/10a(152/147)
814	841	12	4200	4310	159.5	203.5	242	264	286	297	308	352	177	130	10A	12A	374/11
882	14	4565	174	222	264	288	312	324	336	384	204	150	12A				374/12
898	14	4705	188.5	240.5	286	312	338	351	364	416	204	150	12A				374/13
914	14	4950	203	259	308	336	364	378	392	448	252	185	12A				374/14
960	14	5085	217.5	277.5	330	360	390	405	420	480	252	185	12A				374/15

☆ ☆ ☆ Ref to page 25

☆ ☆ ☆ رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	8 Inch	☆ قطر لوله خروجی	Check Valve	6-11 Inch	رزه سوپاپ
------------------	--------	------------------	-------------	-----------	-----------

☆ وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h)								☆ توان نامی Nom. Power		موتور Motor	پمپ Pump			
			آبدهی								HP	kW					
			140	120	100*	90	80	60	0	ارتفاع (m)							
154	10	1775	21	30	37	40	42	45	55	20	15	7A	384/2				
180	10	1995	22	32	43.5	48	51	56	70.5	25	18.5	7A	384/3a(131/127)				
233	260	10	12	2260	2110	31.5	45	55.5	60	63	67.5	82.5	33	24.5	8A	9A	384/3
269	286	10	12	2600	2320	38	52	66	72	76	82	100	41	30	8A	9A	384/4a(136/132)
269	286	10	12	2600	2320	42	60	74	80	84	90	110	41	30	8A	9A	384/4
297	319	10	12	2820	2560	52.5	75	92.5	100	105	112.5	137.5	50	37	8A	9A	384/5
335	352	10	12	3130	2800	63	90	111	120	126	135	165	62	45.5	8A	9A	384/6
375	369	10	12	3490	3010	73.5	105	129.5	140	147	157.5	192.5	75	55	8A	9A	384/7
396	411	12	12	3160	3230	84	120	148	160	168	180	220	85	62.5	9B	9A	384/8
424	446	12	12	3410	3510	94.5	135	166.5	180	189	202.5	247.5	100	73.5	9B	9A	384/9
446	486	12	12	3690	3790	105	150	185	200	210	225	275	100	73.5	9B	9A	384/10
479	520	12	12	3930	3880	111.5	165	203.5	220	231	247.5	302.5	125	92	9B	10A	384/11
490	531	12	12	4070	4020	126	180	222	240	252	270	330	125	92	9B	10A	384/12
523	567	12	12	4220	4140	136.5	195	240.5	260	273	292.5	357.5	150	110	9B	10A	384/13
545	598	12	12	4500	4420	147	210	259	280	294	315	385	150	110	9B	10A	384/14
776	803	12	14	4660	4715	157.5	225	277.5	300	315	337.5	412.5	177	130	10A	12A	384/15

☆ ☆ ☆ Ref to page 25

☆ ☆ ☆ رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	6 Inch	* قطر لوله خروجی	Check Valve	5-11 Inch	رزه سوپاپ
------------------	--------	------------------	-------------	-----------	-----------

☆ وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h)								☆ توان نامی Nom. Power		موتور Motor	پمپ Pump				
			آبدهی								HP	kW						
			90	80	70	60*	50	40	30	0					ارتفاع (m)			
96	10	1320	6	10	12	14	16	17	19	21	5	3.7	6E	335/1				
119	10	1585	13	19	24	29	32	34	37	43	10	7.5	6E	335/2				
158	10	1705	19	29	37	43	48	52	56	65	15	11	7A	335/3				
181	10	1920	25	38	49	57	64	70	75	86	20	15	7A	335/4				
206	10	2120	32	48	61	72	80	87	93	107	25	18.5	7A	335/5				
223	10	2290	38	57	73	86	96	105	112	130	30	22	7A	335/6				
307	280	12	10	2480	2630	45	67	85	100	112	122	131	150	33	24.5	9A	8A	335/7
340	323	12	10	2670	2949	51	77	98	115	128	140	150	172	41	30	9A	8A	335/8
348	331	12	10	2790	3070	57	86	110	129	144	157	168	193	41	30	9A	8A	335/9
380	358	12	10	3005	3265	64	96	122	143	160	175	187	215	50	37	9A	8A	335/10
391	369	12	10	3120	3380	70	105	134	158	176	192	206	236	50	37	9A	8A	335/11
433	416	12	10	3340	3670	76	115	146	172	193	210	224	258	62	45.5	9A	8A	335/12
442	425	12	10	3460	3790	83	125	159	186	209	227	243	280	62	45.5	9A	8A	335/13
451	434	12	10	3580	3910	89	134	171	200	225	245	262	301	62	45.5	9A	8A	335/14
487	493	12	10	3765	4245	95	144	183	215	241	262	280	322	75	55	9A	8A	335/15
497	503	12	10	3880	4360	102	153	195	229	257	279	299	344	75	55	9A	8A	335/16
508	514	12	10	4000	4480	108	163	207	243	273	297	318	365	75	55	9A	8A	335/17
511	526	12	10	4130	4200	114	172	220	258	289	314	337	387	85	62.5	9B	9A	335/18
543	558	12	10	4250	4320	121	182	232	272	305	332	355	408	85	62.5	9B	9A	335/19
546	568	12	10	4240	4340	127	192	244	286	321	350	374	430	100	73.5	9B	9A	335/20
557	579	12	10	4360	4460	134	201	256	301	337	367	393	451	100	73.5	9B	9A	335/21
568	590	12	10	4475	4575	140	211	268	315	353	385	411	473	100	73.5	9B	9A	335/22
559	600	12	10	4980	4930	146	220	281	329	369	402	430	495	125	92	9B	10A	335/23
569	610	12	10	5100	5050	153	230	293	344	385	420	450	516	125	92	9B	10A	335/24

☆ ☆ ☆ Ref to page 25

☆ ☆ ☆ رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	4 Inch	* قطر لوله خروجی	Check Valve	4-11 Inch	رزه سوپاپ
------------------	--------	------------------	-------------	-----------	-----------

✱ وزن کل Total Weight (kg)	✱ قطر چاه Well Dia. (In)		✱ طول کلی Total Length (mm)		Capacity (m <sup>3</sup> /h)						✱ توان نامی Nom. Power		✱ موتور Motor	✱ پمپ Pump			
					110			70*			30				HP	kW	
					Head			ارتفاع			0						
128	10	1590	16	23	27	30	32	34	38	10	7.5	6E	277/2a(127/123)				
147	10	1520	17	24	30	33	36	37	41	12.5	9.2	7A	277/2				
167	10	1705	24	34	41	45	49	51	57	15	11	7A	277/3a(127/123)				
179	10	1805	27	37	46	50	54	56	61	20	15	7A	277/3				
189	10	1920	32	45	55	60	65	68	76	20	15	7A	277/4a(127/123)				
204	10	2000	34	49	61	67	72	74	81	25	18.5	7A	277/4				
284	257	12	10	2240	2390	40	61	76	84	90	93	101	33	24.5	9A	8A	277/5
310	293	12	10	2435	2715	48	73	91	100	108	112	122	41	30	9A	8A	277/6
320	303	12	10	2550	2830	55	79	96	106	114	119	95	41	30	9A	8A	277/7a(127/123)
320	303	12	10	2550	2830	56	86	106	117	126	130	142	41	30	9A	8A	277/7
330	313	12	10	2670	2950	63	90	110	121	130	135	152	41	30	9A	8A	277/8a(127/123)
352	330	12	10	2770	3030	64	98	121	134	144	149	162	50	37	9A	8A	277/8
384	367	12	10	2990	3320	72	110	137	151	162	168	182	62	45.5	9A	8A	277/9
394	377	12	10	3105	3435	80	122	152	167	179	186	203	62	45.5	9A	8A	277/10
421	427	12	10	3295	3775	88	135	167	184	197	205	223	75	55	9A	8A	277/11
441	447	12	10	3530	4010	103	147	178	196	211	220	240	75	55	9A	8A	277/13a(127/123)
431	437	12	10	3410	3890	96	151	182	201	215	223	244	75	55	9A	8A	277/12
446	461	12		3540	3610	104	159	197	218	233	242	264	85	62.5	9B	9A	277/13
466	481	12		3775	3845	119	169	206	226	243	254	272	85	62.5	9B	9A	277/15a(127/123)
456	471	12		3660	3730	112	171	212	234	251	261	284	85	62.5	9B	9A	277/14
483	505	12		3885	3985	120	184	228	251	269	279	305	100	73.5	9B	9A	277/15
493	515	12		4000	4100	128	196	243	268	287	298	325	100	73.5	9B	9A	277/16
503	525	12		4120	4220	136	208	258	285	305	316	345	100	73.5	9B	9A	277/17
494	535	12		4390	4340	144	220	273	301	323	335	365	125	92	9B	10A	277/18
504	545	12		4510	4460	152	233	288	318	341	354	386	125	92	9B	10A	277/19
514	555	12		4625	4575	160	245	304	335	359	372	406	125	92	9B	10A	277/20
564	608	12		5010	4960	176	269	334	368	395	410	426	150	110	9B	10A	277/22
584	628	12		5250	5200	192	294	364	402	431	447	463	150	110	9B	10A	277/24

✱ ✱ ✱ Ref to page 25

✱ ✱ ✱ رجوع شود به صفحه ۲۵

Outlet Pipe Dia.	4 Inch	* قطر لوله خروجی	Check Valve	4-11 Inch	رزه سوپاپ
------------------	--------	------------------	-------------	-----------	-----------

وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h)						* توان نامی Nom. Power		مونور Motor	پمپ Pump				
			آبدهی						HP	kW						
			75	60	50*	30	25	0								
			Head (m)						ارتفاع							
106	10	1320	9	12	13	15	16	18	5	3.7	6E	275/1a(125/121)				
106	10	1320	9	12	14	16	17	19	5	3.7	6E	275/1				
123	10	1515	18	23	27	31	32	36	7.5	5.5	6E	275/2a(125/121)				
128	10	1590	18	25	28	33	34	38	10	7.5	6E	275/2				
147	10	1635	26	35	40	46	48	54	12.5	9.2	7A	275/3a(125/121)				
157	10	1705	27	37	42	50	51	57	15	11	7A	275/3				
167	10	1820	35	47	53	62	63	72	15	11	7A	275/4a(125/121)				
173	10	1860	37	50	56	67	68	76	18	13	7A	275/4				
183	10	1980	44	59	66	77	79	90	18	13	7A	275/5a(125/121)				
204	10	2120	46	62	70	83	86	95	25	18.5	7A	275/5				
214	10	2240	55	74	85	100	103	114	25	18.5	7A	275/6				
230	10	2405	64	87	99	117	120	133	30	22	7A	275/7				
330	313	12	10	2670	2950	73	99	113	133	137	152	41	30	9A	8A	275/8
325	308	12	10	2730	3010	79	105	119	139	143	171	41	30	9A	8A	275/9a(125/121)
340	323	12	10	2790	3070	82	111	127	150	154	190	41	30	9A	8A	275/9
372	350	12	10	3005	3265	92	124	141	166	171	209	50	37	9A	8A	275/10
382	360	12	10	3120	3380	101	136	155	183	188	228	50	37	9A	8A	275/11
404	387	12	10	3340	3670	110	149	169	200	205	247	62	45.5	9A	8A	275/12
414	397	12	10	3460	3790	119	161	183	216	222	266	62	45.5	9A	8A	275/13
424	407	12	10	3580	3910	128	173	197	233	240	285	62	45.5	9A	8A	275/14
451	457	12	10	3765	4245	137	186	211	250	257	304	75	55	9A	8A	275/15
461	467	12	10	3880	4360	146	198	226	266	274	323	75	55	9A	8A	275/16
471	477	12	10	4000	4480	156	210	240	283	291	342	75	55	9A	8A	275/17
486	501	12	10	4130	4200	165	223	254	300	308	361	85	62.5	9B	9A	275/18
496	511	12	10	4250	4320	174	235	268	316	325	380	85	62.5	9B	9A	275/19
506	521	12	10	4365	4435	183	248	282	333	342	399	85	62.5	9B	9A	275/20
536	558	12	10	4590	4690	192	260	296	350	359	415	100	73.5	9B	9A	275/21
546	568	12	10	4710	4810	201	272	310	366	376	437	100	73.5	9B	9A	275/22
556	578	12	10	4830	4930	211	285	324	383	394	456	100	73.5	9B	9A	275/23
588	629	12	10	5050	5000	221	298	338	400	412	475	125	92	9B	10A	275/24
598	639	12	10	5165	5115	231	311	352	417	430	494	125	92	9B	10A	275/25

\* \* \* Ref to page 25

\* \* \* برچوع شود به صفحه 25

Outlet Pipe Dia. 4 Inch قطر لوله خروجی \* ۱۴ Check Valve 4-11 Inch رزوه سوپاپ

وزن کل Total Weight (kg)	قطر چاه Well Dia. (In)	طول کلی Total Length (mm)	Capacity (m <sup>3</sup> /h)							* توان نامی Nom. Power		مونور Motor	پمپ Pump	
			آبدهی							HP	kW			
			50	45	40*	35	30	25	20					0
			Head (m)							ارتفاع				
75	8	1370	8.3	10.5	12	14	15	16	17	20	5	3.7	6E	271/2
80	8	1480	13	15.5	17.5	20	22	23	25	29.5	5	3.7	6E	271/3
92	8	1670	17	21	25	28	30	32	33	39.5	7.5	5.5	6E	271/4
97	8	1780	22	26	31	34	38	40	43	49.5	7.5	5.5	6E	271/5
107	8	1955	26	31	37	42	45	48	50	59	10	7.5	6E	271/6
112	8	2065	30	37	43	49	52	56	59	69	10	7.5	6E	271/7
136	10	2100	34	42	49	55	60	64	67	79	12.5	9.2	7A	271/8
141	10	2210	38	47	54	61	66	71	75	89	12.5	9.2	7A	271/9
156	10	2395	43	52	62	70	76	80	84	99	15	11	7A	271/10
161	10	2505	47	58	66	75	81	87	92	108	15	11	7A	271/11
178	10	2655	52	64	72	82	88	95	101	120	18	13	7A	271/12
183	10	2765	56	69	78	89	96	103	108	130	18	13	7A	271/13
194	10	2935	61	75	84	96	103	111	117	140	20	15	7A	271/14

\* \* \* Ref to page 25

\* \* \* برچوع شود به صفحه 25

Outlet Pipe Dia. 4 Inch قطر لوله خروجی \* ۱۴ Check Valve 3-11 Inch رزوه سوپاپ